

SISCON TMT

Dia/mm	Kg/m	Dia/MM	Kg/M	Dia/mm	Kg/m
6	0.222	8	0.395	10	0.617
12	0.888	16	1.580	20	2.470
25	3.850	28	4.830	32	6.310


BILLETS

125	x	125 mm	—	8.0 - 10.4 mts
75	x	75 mm	—	6.0 - 12.0 mts
65	x	65 mm	—	6.0 - 12.0 mts
90	x	90 mm	—	6.0 - 12.0 mts


GRADES


SISCON TMT	:	Fe - 450 , Fe-500 , Fe-550
BILLETS	:	Mild Steel, Low, Medium & High Carbon, Spring Steel, High Mn & Forging Quality Steels
ROUNDS	:	Mild Steel, Low, Medium Carbon, Bright Bar & Forging Quality
REBARS	:	Thermo Mechanically Treated (TMT) bars of different yield strengths
STRUCTURALS	:	Structural Steel and high tensile Steel
WIRE RODS	:	Low Carbon, Wire drawing, Bright Bar, Electrode Quality, Cold Heading Quality, Tyre-bead and other High Carbon Grades.

PACKAGING




BUNDLE WEIGHTS
4.5 tonnes to 10 tonnes (max)





(NESTED AND INTERLOCKED)



(compacted, coil wight 1.2 MT approx)

WIRE RODS

5.5, 6, 6.5, 7, *7.5, 8, *9, 10, *11, 12, 12.7, *13, 14 mm

ROUNDS

16, *16.5, *17.5, 18, 20, **20.64, 22, 25, 28, 32, 33.5, 34, 36, 38, 40, 42, 45, 46.5, 48, 50, 53, 56, 60, 63, 65, 71, 75, 77, 80 mm

REINFORCEMENT BARS

8, 10, 12, mm	in straightened or coil form
16, *18, 20, *22, 25, 28, 32, 36 mm	in straight lengths

ANGLES

50 X	50 X	5 / 6	mm
60 X	60 X	5 / 6	mm
65 X	65 X	6	mm
75 X	75 X	6 / 8	mm
90 X	90 X	6 / 8	mm
100 X	100 X	8 / 10	mm
110 X	110 X	8 / 10	mm

CHANNELS

MC	*40 X	32 X	5.0 mm
MC	75 X	40 X	4.8 mm
MC	100 X	50 X	5.0 mm
MC	125 X	65 X	5.3 mm
MC	150 X	75 X	5.7 mm

BEAMS

IPE - BEAMS	*180 X	91 X	5.3 mm
HE - BEAMS	*120 X	114 X	5.0 mm
ISMB BEAMS	125 X	70 X	5.0 mm
	150 X	75 X	5.0 mm
	175 X	85 X	5.8 mm



SISCO